



## SAFETY DATA SHEET

### SECTION 1- CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

|                                  |  |
|----------------------------------|--|
| <b>Product Name:</b>             | <b>ACU-EPOXY PRIME side-B</b>  |
| <b>Product Composition/ Use:</b> | Epoxy Primer   |
| <b>CAS Number:</b>               | Mixture  |
| <b>Manufacturer Name:</b>        | Advanced Coating Systems, Inc.   |
| <b>Street Address:</b>           | 2230 Towne Lake Pkwy, Bldg.1000 Ste.150<br>Woodstock , GA 30189 Phone: (678)445-0040 |
| <b>Emergency Telephone:</b>      | INFOTRAC 24hrs, (800)535-5053  |

### SECTION 2- HAZARDS IDENTIFICATION

Flammable Liquids 4  
Skin Irritation 2  
Serious Eye Damage  
2A Skin Sensitisation 1

#### PICTOGRAMS



**SIGNAL WORD:** Danger

#### HAZARD STATEMENTS:

Combustible liquid. Causes skin irritation. Causes serious eye damage/irritation. May cause an allergic skin reaction. Contains materials suspected of causing cancer (bound in liquid/paint, not airborne dust).

#### Precautionary Statement

Keep away from flames and hot surfaces. - No smoking. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations.

### SECTION 3- COMPOSITION AND INFORMATION ON INGREDIENTS

| Components                     | Cas No.    | % by Wt |
|--------------------------------|------------|---------|
| Polyamide Resin                | 68410-23-1 | 5-25%   |
| Aromatic Petroleum Distillates | 64742-95-6 | 3-8%    |

#### **SECTION 4- FIRST-AID MEASURES**

**General rules, in case of doubt or if symptoms persist, always call a doctor.**

**Inhalation:** If inhaled, remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen. If symptoms persist, obtain medical advice.

**Ingestion:** Do NOT induce vomiting without medical advice. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a physician.

**Skin contact:** Immediately remove contaminated clothing and shoes. Wash affected areas, including hair, beneath nails and other concealed areas with soap and water. Get medical attention if symptoms occur.

**Eye contact:** Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

#### **SECTION 5- FIRE AND EXPLOSION HAZARDS**

**Extinguishing Media:** Extinguish preferably with dry chemical, carbon dioxide or foam. Water spray/mist may be used. Do not use water jet.

**Special Protective Equipment for Fire-fighters:** Wear self-contained breathing apparatus.

**Products of Combustion:** Thermal decomposition products are toxic and may include oxides of carbon and nitrogen, various hydrocarbons and other irritating or toxic gases.

#### **SECTION 6- ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Wear personal protective equipment. Avoid breathing vapor while spraying. Ensure adequate ventilation. Remove contaminated clothes as soon as possible.

**Environmental:** Prevent spills to enter and spread to drains, sewers, water courses, and soil.

**Spill Clean Up Methods:** Absorb leaking product with sand, earth or other suitable inert material and collect. Dispose of material in accordance with local and provincial standards.

#### **SECTION 7- HANDLING AND STORAGE**

**Usage Precautions:** Avoid spilling, skin and eye contact. Provide good ventilation. Persons susceptible for allergic reactions should not handle this product. Keep from contact with strong oxidizing materials. Do not get on skin or clothing. Do not get in eyes. Do not breathe vapors or spray mist.

**Storage Precautions:** Store in tightly closed container and avoid freezing.

**Storage:** Store at ambient temperature, or between 32 – 98°F (0 – 36°C). Keep in original container.

#### **SECTION 8- EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Control Parameters:** Exposure via the air and normal handling.

Polyamide Resin (CAS # 68410-23-1) Exposure Limit (ACGIH and TLV): None established

Aromatic Petroleum Distillates (CAS # 64742-95-6) Exposure Limit (ACGIH and TLV): None established

**Engineering Measures:** Use local and general exhaust ventilation to minimize airborne concentrations. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operation procedures demand it.

**Personal Protective Equipment:**

**Respiratory Equipment:** If the product is heated or sprayed under manual handling, use NIOSH approved, air-purifying respirator with organic vapor cartridges and N-95 filters. Full face-piece is recommended. None required under normal conditions of use.

**Body and Hands Protection:** Wear suitable gloves: neoprene, nitrile or acrylonitrilebutadiene rubber or PVC.

Wear full chemical suit when manually spraying this material. Change suit or clean gloves if contaminated.

**Eye Protection:** Wear chemical safety goggles / full face shield if there is a potential for splashing.

**Hygiene Measures:** DO NOT SMOKE IN WORK AREA! Wash hands and any other area that may have been exposed at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Dark Gray Liquid  
**Odor:** Aromatic odor  
**Color:** Dark Gray  
**Flash Point:** 144°F / (62°C)  
**Solubility in Water:** Semi-soluble.  
**Specific Gravity:** 1.405 g/ml  
**VOC:** 110 g/L (aromatic petroleum distillates)

## SECTION 10- STABILITY AND REACTIVITY

**Stability:** Stable under normal temperature conditions  
**Conditions to Avoid:** Strong oxidizing agents  
**Hazardous Decomposition Products:** Thermal decomposition products by fire are toxic and may include hydrocarbons and oxides of carbon and nitrogen.

## SECTION 11- TOXICOLOGICAL INFORMATION

**Toxicity Data:** Polyamide Resin CAS # 68410-23-1 (5-25%)

| Test         | Species | Results   |
|--------------|---------|-----------|
| LD50, Oral   | Rat     | >16 ml/kg |
| LD50, Dermal | Rabbit  | 6.5 ml/kg |

### **Potential Acute Health Effects** (see section 2)

**Eyes:** May cause irritation with symptoms of reddening, tearing, stinging and swelling.  
**Skin:** May cause irritation.  
**Inhalation:** If breathing vapor while spraying may cause respiratory tract irritation.  
**Ingestion:** May include burns or abdominal pain, nausea, vomiting, and diarrhea if swallowed.

## SECTION 11- TOXICOLOGICAL INFORMATION – continued

### **Potential Chronic Health Effects**

**Mutagenicity:** No known significant effects or critical hazards.  
**Carcinogenicity:** No data to suggest carcinogenetic potential.  
**Teratogenicity:** No known significant effects or critical hazards.  
**Fertility Effects:** No known significant effects or critical hazards.  
**Sensitization:** No known data to suggest a risk of sensitization.

## SECTION 12- ECOLOGICAL INFORAMTION

**Biodegradation:** Not readily biodegradable.

**Ecotoxicity:** No information available.

## SECTION 13- DISPOSAL CONSIDERATIONS

Not considered as hazardous waste by RCRA criteria (40 CFR 261). Dispose of waste material at an approved waste treatment facility in accordance with applicable local, state and national laws. Do not dispose of waste with normal garbage, or to sewer systems. Empty containers should be decontaminated and passed to an approved recycler.

## SECTION 14- TRANSPORT INFORMATION

**DOT SHIPPING DESCRIPTION:** Roof Coating, Not Regulated.

49CFR: Applicable for domestic transportation by highway and rail, but not air or vessel (See 49 CFR 173.150 (F)(1) (Not regulated in containers containing less than 119 Gallons) (See 49 CFR 173.150 (F)(1)

**Note:** No reportable quantities (RQ) based on the minor composition of this component

## SECTION 15- REGULATORY INFORMATION

### Federal Regulations

#### Hazardous Categories:

**US Toxic Substances Control Act:** All products are on the TSCA inventory

**US EPA CERCLA Hazardous Substances (40 CFR 302):** Components: No RQ components.

#### SARA Section 311/312:

Polyamide Resin: CAS# 68410-23-1; Acute Health Hazard

Aromatic Petroleum Distillates: CAS # 64742-95-6; Acute and Delayed Health Hazard; Fire

**SARA Section 313:** Aromatic Petroleum Distillates.

**SARA Section 302:** No ingredients of this product are listed.

### State Regulations

**California Proposition 65:** There are benzene components in the aromatic petroleum distillates that are known to the state of California to cause birth defects or other reproductive harm.

**Massachusetts, New Jersey or Pennsylvania Right to Know Substances Lists:** Benzene compositions in the Aromatic Petroleum Distillates (3-8% composition).

#### HMIS-Hazardous Materials Identification System:

Health - 1 Flammability - 1 Physical Hazard - 0 PPE – B

#### NFPA – National Fire Protection Association:

Health – 1 Fire – 1 Reactivity – 0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

## SECTION 16- OTHER INFORMATION

|                     |                         |
|---------------------|-------------------------|
| DATE ISSUED:        | 02/01/2016              |
| REVISION:           | 12/17/2015              |
| SDS REF. No:        | Acu-Epoxy Prime side- B |
| REVISION INDICATOR: | 1.2                     |

**For Your Protection:** Advanced Coatings Systems, Inc. warrants only that its products meet the specifications stated in the sales contract. Typical properties, where stated, are to be considered as representative of current production and should not be treated as specifications. While all the information presented in this document is believed to be reliable and to represent the best available data on these products, NO GUARANTY, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE MERCHANTABILITY OR SUITABILITY OR FITNESS OF ANY CHEMICAL COMPOUNDS OR OTHER PRODUCTS OR THE USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. THE USER SHOULD CONDUCT SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE. Liability of Advanced Coatings Systems, Inc. for all claims, whether arising out of breach of warranty, negligence, strict liability, or otherwise, is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. For all products listed, the user should obtain detailed information on toxicity, together with proper shipping, handling, and storage procedures, and comply with all applicable safety and environmental standards. Toxicity and risk characteristics of chemical compounds and other products may differ when used with other materials or in a manufacturing or other process. Those risk characteristics should be determined by the user and made known to handlers, processors, and end users.

**End of Material Safety Data Sheet**